

# DS225-18V



## SPECIFICATIONS

|                             |                |
|-----------------------------|----------------|
| RPM                         | 0-5000         |
| Torque                      | 5Nm            |
| Voltage                     | 18V            |
| Weight w/<br>3.0 Ah Battery | 2.46KG         |
| Height                      | 243.5mm        |
| Length                      | 372.4mm        |
| Width                       | 85.4mm         |
| Drives<br>Per Charge        | 2500           |
| Warranty                    | 5 Year Limited |

## FASTENERS

|                                |             |
|--------------------------------|-------------|
| Screw Lengths                  | 25 - 55mm   |
| Recommended<br>Screw Diameters | 3.5 -4.0 mm |
| Drive Type                     | EA0297 PH2  |
| Senco                          | EA0298 SQ2  |
| DuraSpin bit                   |             |

## INCLUDES

|  |  |
|--|--|
| (2) Drive Bits<br>EA0297, EA0298             |  |
| (2) 3.0 Ah Li-Ion<br>Extended Life Batteries |  |
| Charger                                      |  |
| Plastic Case                                 |  |

## 55mm 18V LI-ION 5000 RPM AUTO-FEED SCREWDRIVER

Powered by an efficient brushless motor, this high speed auto-feed screw gun includes two extended life 3.0 Ah batteries, a quick release feed system with our patented corner fit technology. The DS225-18V also features feed on return - the next screw is aligned with the bit for better line of sight and easier, more accurate screw placement.

## TOOL OVERVIEW

- Patented corner-fit feed system
- Detachable feed system to expose bit for quick reversing
- 5000 RPM high torque brushless motor
- Precise depth of drive adjustment with depth lock
- Quick slide button bit change
- Two 3.0Ah Li-Ion extended life batteries included
- Quick charge battery charger
- Tool-free screw length adjustment
- Variable speed trigger with lock and reverse
- Adjustable belt hook



## APPLICATIONS

For drywall (into wood or light gauge steel studs), subfloor, sheathing, cement board, and underlayment.





- |  |  |  |
|--|--|--|
| <p><b>1 CORNER-FIT FEED SYSTEM</b><br/>Improved line of sight and better corner access</p>                         | <p><b>5 SPEED SELECTION BUTTON (1600 RPM) (DS522, DS722)</b><br/>Quickly decrease the maximum speed for heavy steel applications</p>             | <p><b>9 TOOL FREE ADJUSTABLE NOSE PIECE</b><br/>Single nosepiece for wood and drywall applications with easy-to-read length markings</p> |
| <p><b>2 FEED ON RETURN</b><br/>Screws are in place before you drive for faster and more consistent performance</p> | <p><b>6 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK</b><br/>For consistent flush drive or countersink (knob is on the reverse side, not shown)</p> | <p><b>10 QUICK TOGGLE REVERSE SWITCH</b><br/>Easily switch between forward and reverse</p>   |
| <p><b>3 REMOVABLE FEED SYSTEM</b><br/>Detachable feed system for easier reversing</p>                              | <p><b>7 EXTENDED LIFE 3.0AH LI-ION BATTERY</b><br/>Uses latest cell technology for increased power and capacity</p>                              | <p><b>11 VARIABLE SPEED TRIGGER</b></p>  |
| <p><b>4 HIGH SPEED BRUSHLESS MOTOR</b><br/>Provides increased performance and battery life with reduced size</p>   | <p><b>8 QUICK SLIDE BIT RELEASE</b><br/>Screws are in place before you drive for faster and more consistent performance</p>                      | <p><b>12 PATENTED SCREW GUIDE</b><br/>Prevents screw binding for consistent feeding</p>  |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems visit our website at: [www.senco.com](http://www.senco.com)