



## Applications

Sheathing, furniture framing, roof decking, subflooring, crate and box assembly, pallets, cedar shingles, furring, metal tie-down straps, fascia and soffits, and ridge beam assembly

## Features & Benefits

- 20% more powerful than the standard NS20XP for the most demanding applications
- Narrow line of sight for precise staple placement
- Well-balanced, ergonomic design for all-day use
- Enhanced EZ-Clear latch allows for quick access to clear fasteners
- Precision-machined drive track ensures accurate, jam-free staple drives into all substrates

## Description

NS20BXP-N, hw stapler

## Art. Nr.

9Y2001N

## EAN code

8718035005090


# Heavy wire stapler

## Technical specifications

Dimension (LxWxH)	381x102x279 mm
Net weight	2.6 kg
Firing mode	Dual
Air inlet	3/8" female NPT
Operating pressure	4.8 - 8.3 bar
Air consumption (at 60 shots per minute)	136 l/m
Operating temperature range	-18 - 49 °C
Sound pressure level (Lpa)	87 dB
Sound power level (Lwa)	92 dB
Vibration level	2.7 m/s <sup>2</sup>
Shots / second	10
Magazine capacity	160 pieces
Gauge	16 ga.
Collation type 1	Glue collated
Collation angle	0 °

## Fastener specification

**N staple**  
10,6 mm



**O staple**  
10,6 mm

