













## **Applications**

Truss building, framing, sub-flooring, sheathing and decks. Other applications include crate and box assembly, pallet making and fencing. Great for any application where cordless convenience would be a benefit.

## **Features & Benefits**


- Cordless convenience no hoses, no compressors, no hassles. Navigate the job site with no restrictions
- Powerful motor high-voltage ignition gives you more power and cleaner combustion
- Consistent drives In all Weather conditions performs optimally between -7° to 49°C
- Durable metal magazine rugged design outlasts plastic
- Tool-free, metal thumbwheel depth-of-drive

   easily control fastener depth with no tool required

## **Cordless Framing Nailer**

Technical specifications	
Dimension (LxWxH)	374x108x378 mm
Net weight	3.6 kg
Firing mode	Restrictive
Operating temperature range	-7 - 49 °C
Sound pressure level (Lpa)	96.2 dB
Sound power level (Lwa)	100.8 dB
Vibration level	3.1 m/s
Fastener driving power	85 J
Magazine capacity	70 pieces
Collation type 1	Paper collated
Collation angle	34 º
Battery type	Li-Ion
Battery voltage	7.2V
Battery ampere rating	2.5 Ah
Shots per charge	8000
Number of batteries in kit	2 pieces
Length fuel cell	165 mm
Fuel cell type	40 gram
Shots per fuel cell	1200
Voltage (ac)	230 V
Frequency	50&60 Hz
Electrical plug type	AU/NZ

## **Fastener specification**



Description Art. Nr. EAN code

90mm Framing Gas Tool

4VS2001N