

**SENCO**<sup>®</sup>MAKING HARD WORK  
**EASIER**

## Applications

Major: drawer assembly, countertop buildup, cabinets, corner and glue block fastening, and spring clip attachment in furniture assembly. Widely used in assembly of doors and window casings, trim, and moldings. On-site construction uses for aluminum and vinyl siding, underlayment, and attachment of roofing sheathing and decking materials. Other: light crating, agricultural boxes, fencing, and all types of wood crafts.

## Features & Benefits

## Medium wire stapler

### Technical specifications

|  |                      |
|--|----------------------|
| Dimension (LxWxH)                        | 314x76x238 mm        |
| Net weight                               | 1.9 kg               |
| Firing mode                              | Dual                 |
| Air inlet                                | 1/4" female NPT      |
| Operating pressure                       | 4.8 - 8.3 bar        |
| Air consumption (at 60 shots per minute) | 61.2 l/m             |
| Operating temperature range              | -18 - 49 °C          |
| Sound pressure level (Lpa)               | 86 dB                |
| Sound power level (Lwa)                  | 91 dB                |
| Vibration level                          | 2.5 m/s <sup>2</sup> |
| Fastener driving power                   | 26 J                 |
| Shots / second                           | 5                    |
| Magazine capacity                        | 145 pieces           |
| Gauge                                    | 18 ga.               |
| Collation type 1                         | Glue collated        |
| Collation angle                          | 0 °                  |

### Fastener specification

L staple  
6.4 mm



19-38 mm

### Description

SKSXP-L, mw stapler, restrictive

### Art. Nr.

302020N

### EAN code

0741474301162