

SENCO[®]MAKING HARD WORK
EASIER

Applications

Major: drawer assembly, countertop buildup, cabinets, corner and glue block fastening, and spring clip attachment in furniture assembly. Widely used in assembly of doors and window casings, trim, and moldings. On-site construction uses for aluminum and vinyl siding, underlayment, and attachment of roofing sheathing and decking materials. Other: light crating, agricultural boxes, fencing, and all types of wood crafts.

Features & Benefits

Medium wire stapler

Technical specifications

Dimension (LxWxH)	314x76x238 mm
Net weight	1.9 kg
Firing mode	Dual
Air inlet	1/4" female NPT
Operating pressure	4.8 - 8.3 bar
Air consumption (at 60 shots per minute)	61.2 l/m
Operating temperature range	-18 - 49 °C
Sound pressure level (Lpa)	86 dB
Sound power level (Lwa)	91 dB
Vibration level	2.5 m/s ²
Fastener driving power	26 J
Shots / second	5
Magazine capacity	145 pieces
Gauge	18 ga.
Collation type 1	Glue collated
Collation angle	0 °

Fastener specification

L staple
6.4 mm



19-38 mm

Description

SKSXP-L, mw stapler, restrictive

Art. Nr.

302020N

EAN code

0741474301162