

**SENCO**<sup>®</sup>MAKING HARD WORK  
**EASIER**

## Applications

For upholstery operations and varied component assemblies in furniture manufacturing, such as drawers, casebacks, cabinet frame assembly, and upholstery spring attachment. Used in underlayment sheathing, paneling, molding/trim, soffits, pre-finished gypsum, and siding for on-site and manufactured housing, lattice and bed-spring attachment

## Features & Benefits


- Lightweight for ease of handling
- Ergonomically designed with a comfort-grip handle to reduce fatigue
- Adjustable depth-of-drive for precise staple setting
- Fewer moving parts for less maintenance and minimal downtime
- No-mar pad keeps work surfaces free of marks
- Oil-free design means easier maintenance and no lubrication to stain fine wood
- Muffler ensures quiet operation

## Medium wire stapler

### Technical specifications

Dimension (LxWxH)	305x51x216 mm
Net weight	1.13 kg
Firing mode	Dual
Air inlet	1/4" female NPT
Operating pressure	4.8 - 8.3 bar
Air consumption (at 60 shots per minute)	54.4 l/m
Operating temperature range	-18 - 49 °C
Sound pressure level (Lpa)	80 dB
Sound power level (Lwa)	87 dB
Vibration level	2.5 m/s <sup>2</sup>
Fastener driving power	14.2 J
Shots / second	10
Magazine capacity	168 pieces
Gauge	18 ga.
Collation type 1	Glue collated
Collation angle	0 °

### Fastener specification



### Description

SLS20XP-L, mw stapler

### Art. Nr.

492023N

### EAN code

0741474040269